



## &gt; INTERCEPTION SYSTEMS AND ACCESSORIES

## &gt; RODS AND MESHED CONDUCTORS

## &gt; TAPER POINTED AIR ROD

These air rods are available in copper or aluminium and fit into multi-points (table 11) and into flat and ridge saddles and air rod bases for example AT-104B or AT-110B (tables 16 to 21).

Reference	Dimensions (mm)	Total length (m)	Thread	Includes	Material	Weight (kg)
AT-004A	Ø16 x 350 + Ø15 x 150	0.5	M16	Tightening nut	Copper	0.73
AT-005A	Ø16 x 850 + Ø15 x 150	1	M16	Tightening nut	Copper	1.51
AT-006A	Ø16 x 1850 + Ø15 x 150	2	M16	Tightening nut	Copper	3.00
AT-007A	Ø16 x 350 + Ø15 x 150	0.5	M16	Tightening nut	Aluminium	0.29
AT-008A	Ø16 x 850 + Ø15 x 150	1	M16	Tightening nut	Aluminium	0.53
AT-009A	Ø16 x 1850 + Ø15 x 150	2	M16	Tightening nut	Aluminium	1.06

Complies with IEC 62305, IEC 62561

- AT-004A (Cu - copper)
- AT-007A (Al - aluminium)

