



> UNIONES EQUIPOTENCIALES

> TERMINAL DE ANILLO DE COBRE ESTAÑADO

Los terminales de anillo se utilizan para conectar correctamente un cable mediante tornillos y tuercas.

Referencia	Dimensiones del cable (mm ²)	Tamaño del tornillo	Peso (g)
AT-091K	10	M5	2,2
AT-092K	10	M6	2,0
AT-015K	16	M6	5,0
AT-016K	16	M8	4,0
AT-017K	25	M8	8,0
AT-018K	25	M10	9,0
AT-019K	35	M8	10,0
AT-020K	35	M10	9,0
AT-093K	50	M10	15,0
AT-021K	50	M12	14,0
AT-022K	70	M10	22,0
AT-023K	70	M12	20,0
AT-094K	95	M10	28,0
AT-024K	95	M12	25,0
AT-070K	120	M12	44,5
AT-028K	120	M16	41,0
AT-061K	150	M12	56,0
AT-030K	150	M16	53,0
AT-095K	185	M12	67,0
AT-031K	185	M16	63,0
AT-072K	240	M12	117,0
AT-032K	240	M16	112,0

Cumple con UNE 21186, NF C 17-102, IEC 62305, IEC 62561

Consultar otras medidas



AT-021K